

# FA-10GMC-1SFP+

10G Managed Standalone Fiber Media Converter



## Product Features

- ❖ Supporting 10G full duplex auto-sensing
- ❖ Supporting auto-MDI/MDIX
- ❖ Supporting 10Gbase-T to 10Gbase-SR/LR/ER/ZR
- ❖ 3R function, stable data transmission
- ❖ Short delay time when transparent transmission
- ❖ Supporting Jumbo frame
- ❖ Supporting transmission length of RJ45 network cable

- ❖ Supporting DMI(Diagnostic Monitoring Interface) function of optical transceivers
- ❖ Supporting 850nm, 1310nm, 1550nm and DWDM/CWDM wavelength ruled by ITUT
- ❖ Supporting Loop-back, precisely locating the failure, convenient for link test
- ❖ Economical management function within bandwidth
- ❖ With powerful network management function(Web, SNMP, Console), supporting WEB and SNMP
- ❖ Supporting hot plug
- ❖ Easy installation with complete LED indicators for working situation
- ❖ Supporting 2U chassis (16 slots) and standalone use

## Description

16-slot multifunctional management system is a Ethernet and SDH transmission equipment, support mutiple services including managed media converter card, OEO Converter card, 1+1 protection switching card, CWDM/DWDM MUX/DEMUX Card, etc. , supports protocols like SNMP, WEB, CONSOLE and TELNET , with a strong management function , and operate easily to meet different customer's requirement.

## Specification

Parameters	Specification
<b>Access Method</b>	1X10G RJ45 1X10Gbase-FX
<b>Power Dissipation</b>	<8W
<b>Operating Temperature</b>	0 ~ 50 °C
<b>Humidity</b>	5%~90%
<b>Storage Temperature</b>	-40 ~ 70 °C
<b>Dimension</b>	112.8mm (W)×77.2mm(D)×23 mm(H) (Card)

**Ordering Information**

<b>Part Number</b>	<b>Product Description</b>
FA-10GMC-1SFP+	10G Managed Standalone Fiber Media Converter, SFP+ to RJ45